

LINX 8840 SPECTRUM



Reliable high contrast coding with the Linx 8840 Spectrum

The Linx 8840 Spectrum delivers consistent, high-opacity, error-free codes with low cost of ownership. Advanced features ensure reliability is built-in with the Linx 8840 Spectrum, even after **up to one month shutdown**.

Innovations including **Vortex** and **PureFlow** increase production uptime and extend maintenance intervals whilst delivering high contrast printing. High-speed marking of **up to 10m/s**, and **live message creation and editing while printing** with accurate **'metre marking'** makes the 8840 Spectrum printer ideal for printing pigmented inks onto surfaces such as flexible plastic cabling, extruded plastics, and coloured glass.



Innovative

- ✓ Best in class **extended service interval** of up to **8,000 hours or 12 months**, with a range of inks
- ✓ Patent-pending **PureFlow®** is an innovative, powerful filtration system for opaque print and a cleaner nozzle
- ✓ **Premium print quality**, and trouble-free restarts from patent-pending **Vortex®**, a robust mixing tank with a unique method of re-dispersing the settled heavy pigment



Reliable

- ✓ **Reliable performance**, including in extreme environments and up to **one month shutdown**. The printer is ready to print first time, with no need for flushing or to be permanently powered on
- ✓ Linx robust **sealed printhead** means fewer interventions and less cleaning, typically only **once per week**, even when running continuously
- ✓ **AutoFlush** unique printhead cleaning sequence leaves the printhead and conduit clean and dry, ready for every startup



Easy to Use

- ✓ **Simple user interface** with large, icon-driven touch screen, customisable with product images and with production-rate visibility
- ✓ **Mistake-free**, mess-free, one-touch, fluid cartridge refills during printing
- ✓ **Linx PrinterNet®** ready, for remote monitoring and control via a secure cloud-based service

PRINTHEAD

60mm minimum bend radius in static applications. 180mm minimum bend radius in dynamic applications.



SIDE ELEVATION



FRONT ELEVATION



90° PRINTHEAD OPTION

270 degree adjustable positioning



Technical Specifications

PRINT SPEEDS AND SIZES

Printhead:	Mk11 Midi	Mk11 Midi plus
Nozzle size:	62 µm	75 µm
Lines of print:	Up to 6	Up to 6
Character height range:	1.8 to 16 mm	2.1 to 17 mm
Maximum speed for single line print (5 dot high characters):	7.50 m/s (0.469 mm drop pitch)	9.10 m/s (0.569 mm drop pitch)
Maximum speed for single line print - ultra fast tower print style (5 dot high characters):	-	10 m/s (0.625 mm drop pitch)
Maximum number of characters per second (10m/s speed, 0.625mm pitch):	-	2666
Recommended distance from printhead to substrate:	12 mm	20 mm
Recommended distance from printhead to substrate - for high speed cabling:	-	5 mm

HARDWARE FEATURES

Service module change interval: up to 12 months (8,000 hours)*
Unique AutoFlush automatic printhead flushing and conduit clearing
Sealed printhead typically only requires cleaning once per week**
Printhead jet-speed control and temperature sensing for consistent printing in changing ambient temperatures
Mistake-proof, mess-free ink and solvent refilling while printing (0.5 litre ink cartridge, 1 litre solvent cartridge)
7-inch full colour touch screen with tough, solvent-resistant polymer cover
Fit-for-life ink pump with no scheduled changes required
Extended shutdowns (up to 28 days) without printer flushing or draining
Robust, flexible dual-tube conduit for static and moving printhead applications

SOFTWARE FEATURES

Single-press start print, pause print and jet shutdown
Auto power-off after jet shutdown
Simple message creation and editing with drag-and-drop field positioning, zoom function and insert mode for long messages
Total print count, message count and batch count
Message store display and message style selection
Password-protected functions, with customisable user profiles
Message creation/editing while printing

On-screen output rate measurement and production stoppage log. Downloadable onto USB

On-screen fluid level indicators, 12 hour running from fluid refill warning to printer stop in most applications

On-screen help and diagnostics information

PrintSync® automatic font and message format selection, based on message style selected and production line speed

Multiple operator languages (user selectable) with on-screen keyboards, secondary keyboard for multi-language printing

Simple line speed and shaft encoder setup wizard, for installation on new production lines

Up to 50 lines settings can be stored, with individual line names with guided step by step line setup wizard

Dynamic orientation for printing on traverse applications

Message store and printer settings backup, copy and restore using USB storage device

Saving remote field data over a power cycle

Linx Remote Communications Interface for connection to PCs or PLCs using Ethernet port

QuickSwitch® message selection, remote field update and message select-and-populate text field, using barcode scanner

Linx PrinterNet printer health and production monitoring with remote control (VNC) (option)

MESSAGE PRINTING FACILITIES

Text, symbols and numbers
Prompted fields for one-step message editing with customisable on-screen prompts
Height, width and delay functions for easy code sizing and positioning
Automatic formats for printing dates, times and date rounding (using the printer's internal clock)
Custom date and time editor to create different date formats as required
Automatic date forward function. Add number of seconds, minutes, hours to the current time, or number of days, weeks or months to the current date
Automatic time adjustment option for daylight savings time
Sequential numbering, forward and backward counting, variable intervals, multiple number ranges, alphanumeric sequencing
One touch sequential number reset option from the printer screen, and reset using external trigger
Sequential text fields, increment and reset sequences using external triggers, optional one touch sequence reset from the printer screen
'Production Schedule' function, to print a sequence of messages automatically, with different orientation, repeat and delay options
Number of messages stored: up to 1000 using internal printer memory (depending on message content), more can be stored using a USB storage device
Variable character spacing for improved readability and vision system recognition
Rotated character (tower) printing
Reverse and inverted printing

Accurate marking at regular intervals i.e. 'metre marking', with rollback to detect lines running backwards and high precision calculation options

Logos and graphics can be imported into the printer as monochromatic bitmap files using the USB port

Shift coding (message content changes automatically at defined times)

Barcodes (ITF 2 of 5, Code 39, Code 128, EAN 13, EAN 8, UPCA, Pharmacode, Data Matrix, QR Code, RM4SCC-Type C)

PRINTHEAD OPTIONS

2m conduit
4m conduit (option)
90° printhead configuration (option)
Positive air purge to printhead (provides improved reliability in dusty or humid environments) (option)
Air dryer (provides improved reliability for certain inks at high humidity and temperature) (option)

INK RANGE

Linx MEK base high opacity pigmented inks

CONNECTIONS/INTERFACING FOR

Product detector
Shaft encoder/secondary product detector
Multiple printer triggering from single product detector/shaft encoder including quadrature encoders for directional applications
USB - for printer settings and customer data backup, and Wi-Fi connection for Linx PrinterNet
Ethernet - for Remote Communications Interface and Linx PrinterNet
Volt-free contact alarm connection (e.g. for use with external mains-driven alarm) (option)
External single-stage alarm output (24V)
Dual alarm output (Volt-free and/or 24V output) (option)

PHYSICAL CHARACTERISTICS

Base and enclosure: Stainless steel
IP55 environmental protection rating***
Mounting options: Static stand, mobile stand, bench, shelf for wall mounting
Operating temperature range: 5 - 45°C
Humidity range (r.h., non-condensing): 90% max
Power supply: 100-230V, 50/60Hz
Power consumption: 38W (typical when printing)
Power rating: 120 W
Weight: 23kg (including fluids and 2m printhead)

REGULATORY APPROVALS

• CE • UL • CAN/CSA • FCC • BIS

*Interval may be adjusted in certain environments and applications to provide reliable running between service module changes
**When printing up to 16 hours a day, 5 days a week
***IP rating is independently verified - certificates available on request



PRINT JET®

PRINT JET SOLUTIONS LLP®

Corporate Office : #22, Huliappa Arcade, 2nd Floor, 2nd Block, Nagarbhavi 2nd Stage, Bangalore-72

Contact : +91 9686861933, +91 88615 88815, +91 80 29773733

Email : info@printjetsolutions.in **Web :** www.printjetsolutions.in

LINX